



K-TEC
EARTHMOVERS AUSTRALIA

1225 & 3100

STRENGTH DURABILITY PERFORMANCE

**K-Tec Earthmovers providing quality
earthmoving equipment for sale and hire**



PRODUCT	1225 imperial	1225 metric	3100 imperial	3100 metric
Horsepower Required	350 +	261 kW +	400 +	298 kW +
Bucket Dimensions	12'W x 4'H x 10.5'L	3.65mW x 1.22mH x 3.20mL	12'W x 5'H x 11'L	3.65mW x 1.52mH x 3.35mL
Rack Height	3'	0.91m	4'	1.22m
Struck Capacity	18.5 Cu. Yds	14.1m ³	24 Cu. Yds	18.3m ³
Heaped Capacity	28 Cu. Yds	21.4m ³	36 Cu. Yds	27.5m ³
Cutting Width	12'	3.65m	12'	3.65m
Overall Width	13' 10"	4.22m	13' 10"	4.22m
Overall Length	32' 10"	10m	36' 4"	11.07m
Shipping Weight	24,000 lbs	10 886kg	26,800 lbs	12 156kg
Hitch to Axle Length	28'	8.5m	30' 11"	9.42m
Weight Distribution	Tongue 25% Wheels 75%	Tongue 25% Wheels 75%	Tongue 25% Wheels 75%	Tongue 25% Wheels 75%
Apron Opening	78"	1.98m	84"	2.13m
Cutting				
Edge Clearance	26"	0.66m	30"	0.76m
Tyres x 4	23.5 x 25	597mm x 635mm	23.5 x 25	597mm x 635mm
Apron Cylinders	4" x 28"	102mm x 711mm	4.5" x 28"	114mm x 711mm
Lift Cylinders	5.5" x 31"	140mm x 787mm	5.5" x 38"	140mm x 965mm
Ejector Cylinder	5" x 76"	127mm x 1930mm	5.5" x 76"	140mm x 1930mm
Cutting Edge	3-Piece Blade	3-Piece Blade	3-Piece Blade	3-Piece Blade
Stinger Size	6', 7' & 8'	1.83m, 2.13m, 2.43m	6', 7' & 8'	1.83m, 2.13m, 2.43m
Laser Bracket Mount	Standard	Standard	Standard	Standard
Ride Control	Standard	Standard	Standard	Standard
Push Block	Standard	Standard	Standard	Standard
Radial Tyres	Optional	Optional	Optional	Optional
Skid Shoes	Optional	Optional	Optional	Optional
Mud Scrapers	Optional	Optional	Optional	Optional
Cushion Hitch	Optional	Optional	Optional	Optional



PO Box 1441, Griffith, NSW, 2680
p: 1800 KTECOZ
m: 0428 696 071
e: admin@ktecearthmovers.com.au

www.ktecearthmovers.com.au