



K-TEC
EARTHMOVERS AUSTRALIA

1233

STRENGTH

DURABILITY

PERFORMANCE

**K-Tec Earthmovers providing quality
earthmoving equipment for sale and hire**



PRODUCT 1233 imperial 1233 metric

Horsepower Required	400 +	298 kW +
Bucket Dimensions	12'W x 4' 3"H x 12' 10"L	3.65mW x 1.29mH x 3.91mL
Rack Height	4'	1.22m
Struck Capacity	19.7 Cu. Yds	15m ³
Heaped Capacity	33 Cu. Yds	25.2m ³
Cutting Width	14'	4.26m
Overall Width	14'	4.26m
Shipping Weight	28,000 lbs	12 700kg
Overall Length	38'	11.58m
Hitch to Axle Length	31' 4"	9.55m
Weight Distribution	Tongue 23%	Tongue 23%
	Wheels 77%	Wheels 77%
Apron Opening	80"	2.0m
Cutting		
Edge Clearance	28"	0.71m
Tyres x 4	23.5 x 25	597mm x 635mm
Apron Cylinders	5" x 28"	127mm x 711mm
Lift Cylinders	5.5" x 31"	140mm x 787mm
Ejector Cylinders	5.5" x 76"	140mm X 1930mm
Cutting Edge	3-Piece Blade	3-Piece Blade
Stinger Size	6', 7' & 8'	1.83m, 2.13m, 2.43m
Laser Bracket Mount	Standard	Standard
Ride Control	Standard	Standard
Push Block	Standard	Standard
Radial Tyres	Optional	Optional
Mud Scrapers	Optional	Optional
Cushion Hitch	Optional	Optional
Underslung Hitch	Optional	Optional



*THIS MODEL IS ALSO AVAILABLE AS A TANDEM UNIT (TDM)

PO Box 1441, Griffith, NSW, 2680
p: 1800 KTECOZ
m: 0428 696 071
e: admin@ktecearthmovers.com.au

www.ktecearthmovers.com.au